

Product Features

P1-SMAPRA/SMAPRA-085CJ-5 is an RF Cable that is part of P1dB's YouForm™ conformable cable assembly series. It is a 5 inch SMA Male Right Angle to SMA Male Right Angle Jacketed Conformable cable assembly that utilizes 085CJ conformable coax with a diameter of 0.102 inches. The RF cable assembly operates to 18 GHz with a max VSWR of 1.35:1. YouForm™ cables are conformable and jacketed conformable versions 085 and 141 semi-rigid coax cables and meet RG402 and RG405 dimensional and electrical specifications. YouForm™ cable assemblies can operate up to 18 GHz, depending on the configuration. The advantage of YouForm™ conformable cables over semi-rigid are their ability to be formed by hand multiple times, while semi-rigid cables can be formed only once with special bending tools.



Electrical Specification: T_{Ambient} = 25° C

Parameter	Frequency Range	Units	Min	Typical	Max	Notes
Frequency Range		GHz	DC		18.0	
VSWR	DC to 1.0	1:			1.2	
	1.0 to 5.0				1.25	
	5.0 to 10.0				1.26	
	10.0 to 18.0				1.35	
Insertion Loss	DC to 1.0	dB/ft.			0.22	
	1.0 to 5.0				0.49	
	5.0 to 10.0				0.83	
	10.0 to 18.0				1.18	
Velocity Of Propagation		%		70.0		

Mechanical And Environmental Specifications:

Parameter	Description	Notes
Connector 1	SMA Male Right Angle	
Connector 1 Coupling Nut	Passivated Stainless Steel	
Connector 1 Body	Gold Plated Brass	
Connector 1 Contact	Gold Plated Brass	
Connector 2	SMA Male Right Angle	
Connector 2 Coupling Nut	Passivated Stainless Steel	
Connector 2 Body	Gold Plated Brass	
Connector 2 Contact	Gold Plated Brass	
Coax Cable	Jacketed Conformable	
Cable Type	085CJ	
Cable Inner Conductor	SPCW	
Dielectric	PTFE	
Shield	1. Tinned Cu/Sn Braid	
Jacket	FEP	

SMA Male Right Angle to SMA Male Right Angle cable assembly using 085CJ Jacketed
Conformable Coax, 5 inches long, Operating to 18 GHz.

Parameter	Description	Notes
Coax Diameter	0.102	
Minimum Bend Radius	0.38	
Length	5.0	
Operating Temperature	-85.0 to 200.0 °C	
RoHS Compliance	Yes	

Drawing



Product Notes